

MCI4000

2MP Indoor IP/Network IR Mini Vandal Dome Camera

- Up to 2MP high resolution
- Max. 1920*1080@30fps(50Hz/60Hz)
- Day/Night, AWB/MWB,BLC, 3D-DNR,Shutter, IR-CUT,D-WDR,WDR,Mirror, Image Flip etc.

Functions

- 3.6mm fixed lens
- IR range: up to 12m
- Water-proof: IP66
- Verification to :BS EN 62676-1-1-2014 – Video surveillance systems for use in security applications



DIMENSIONS



SPECIFICATION

Camera	
Image Sensor:	1/2.8" Sony307 2MP CMOS
Signal System:	PAL/NTSC
Min. Illumination:	Color: 0.05lux @(F1.2, AGC ON), 0 lux with IR
Shutter Time:	1/25 s to 1/10,000 s
Lens:	3.6mm fixed lens
Day&Night:	IR cut filter with auto switch
Image Enhancement:	BLC/3D DNR/D-WDR/WDR
Motion Detection	Support
Privacy Protection	Support(4 Self-customized Areas)
Water-Proof:	IP66
Illumination for Infrared	1~5Lux
Switching:	
Infrared Wavelength:	850nm
Minimum Illumination:	0 Lux(IR ON)
IR Range:	12pcs LEDs//12m IR
Compression Standard	
Video Compression:	H.265/H.264
Video Bit Rate:	512Kbps~3072Kbps(main stream H.265) 64Kbps~512Kbps(sub stream H.265)
Audio Compression:	G711U/G711A/AAC
Dual Streams:	Yes
Triple Streams:	No
Image	
Max. Image Resolution:	1920*1080@30fps(2MP)
Frame Rate:	30fps(2MP).MAX main stream 30fps (D1) .MAX sub stream
Image Settings:	3D NR, D-WDR, Image Flip, Saturation, Brightness, Contrast, Sharpness adjustable via client software, web browser or Smartphone App
Day/Night Switch:	EXT/Day/Night/Auto/Time
Audio	
Line IN/line OUT:	Support (1ch)
Build-in MIC:	Optional
Volume adjust:	Yes
Network	
Network Protocols:	HTTP, TCP/IP, IPv4/v6, UPNP, RTSP, UDP, SMTP, NTP, DHCP, DNS,DDNS,IP Search(Support P2P, NVR, NVS etc.)
System Compatibility:	ONVIF(17.2 with profile S)
On-line Viewing	Max. Support 2 Users Simultaneously
Interface	
Communication Interface:	1 RJ45 10M / 100M Ethernet Interface
RCA Audio Interface:	RCA Audio input/output Interface (Optional)
Alarm in/out interface:	Support (1ch) (Optional)
DC Power Plug:	DC Power Female Interface
General	
Operating Conditions:	-10 °C ~ 60 °C
Power Supply:	Humidity 95% or less (non-condensing) 12 V DC ± 10%/PoE
Power Consumption:	12 VDC ± 10%, Max Power Consumption Less than 8W (When the infrared lamps turn on)
Weight:	0.45KG