

ULTRA-LOW-POWER ULTRASONIC PRO WIND SENSOR (ULP PRO)



Power: 3..3 - 18 VDC

Information Given:

- Wind Speed

Range: 0.5 - 45 m/s (1.12 to 100 mph)

Accuracy: 0.1 m/s at 10 m/s (0.22 in. at 22 mph)

Threshold: 1 m/s (2.24 mph)

- Wind Direction:

Range: 0- 359°

Accuracy: $\pm 1^\circ$ RMS at 10 m/s (22.37 mph)

Measurement:

- Power Consumption

(UART) 0.15 mA at 38,400 bauds, 1 Hz (5V)

(RS485) 0.25 mA at 38400 bauds, 1 Hz (5V)

Baudrate: 2,400 to 115,200 (8n1) bauds

Output rate: 0.1 to 20 Hz

Output units: m/s, Knots, or Km/h

Easy Mount

- 2xM3 lateral female tripod thread UNC1/4"-20

- 3xM3 base female tripod thread UNC1/4"-20 UNC1/4"-20

Sensor:

Ultrasonic Transducers (4x)

Dimensions:

Diameter: 68 mm (2.68 in.)

Height: 65 mm (2.55 in.)

Weight: 200 grams (7.05 oz.)

Environmental:

- IP Protection IPX8

- Temperature Range

-15/55° C (5/131° F) if no frost

Firmware upgradable. Configurable via cable.

If you require a cable length longer than 20 meters (MODBUS), we can provide support. Please contact our technical support team for assistance.

Data Output:

SKU

- RS485 (NMEA 0183)/ MODBUS

-Stream or Poll

CMI1019

- UART (NMEA 0183)

CMI1032

- DAVIS compatible

-Stream or Poll



ULP PRO SPECS SHEET



English version 1.0
25.05.2023

C/Alfonso Solans Serrano 20, local 12,
Zaragoza, Spain 50014
+34 976 291 839
sales@calypsoinstruments.com

2655 S. Le Jeune Road, Ste #905
Coral Gables, Florida USA 33134
+1(786) 321-4334 /+1(786) 321-4793
sales@calypsoinstruments.com